

## Cable Ties

### Bar-Lok



#### SPECIFICATION

#### UL

#### APPLICATIONS

- Multi-purpose
- For high impact and tensile strength

#### CONSTRUCTION

**Material:** Flame retardant 6/6 nylon

**Temperature:** -40°C to 80°C

Part Number	Length (in.)	Colour	Features	Bundle Diameter (min & max, in.)	Tensile Strengths (lbs)	Package Qty (per bag)
63-F08432	4	Natural	-	1/16-7/8	18	1000
63-F08433	4	Black	Weather resistant	1/16-7/8	18	1000
63-F08376	5.5	Natural	-	1/16-1-1/4	40	1000
63-F08431	5.5	Black	Weather resistant	1/16-1-1/4	40	1000
63-F08387	7.5	Natural	-	1/16-1-3/4	50	1000
63-F08388	7.5	Black	Weather resistant	1/16-1-3/4	50	1000
63-F08415	7.5	Natural	Screw Mount	1/16-1-3/4	50	1000
63-F08600	11	Natural	-	1/16-3	50	1000
63-F08286	11	Black	Weather resistant	1/16-3	50	1000
63-F10039	14.5	Black	Weather resistant	3/16-4	120	100
63-F10037	15	Black	Weather resistant	1/16-4	50	500
63-F10608	21	Black	Weather resistant	1/4-6	120	50
63-F10614	24	Black	Weather resistant	1/4-7	120	50
63-F10620	28	Black	Weather resistant	1/4-8	120	50
63-F10050	34	Black	Weather resistant	1/4-10	175	50

*Note: All dimensions are nominal and are subject to normal manufacturing tolerance.  
Specifications are subject to change without prior notice*