

## Ultraflex Split Loom Polyethylene



### APPLICATION

- Mechanical, chemical and electrical protection

### CONSTRUCTION

- Material:** Durable Polyethylene, black
- Construction:** Slit allows quick installation without the need of fishing wires
- Variation:** Non-slit also available to give a better protection from environmental elements
- Temperature:** -40°C to 93°C
- Feature:** Resistant to oil and gas, moisture, UV light, salt and abrasion
- Option:** Packaged in 2'sq boxes or 4'sq gaylords. Cut to length packaging also available  
Other colours available upon request

| Box Part Number<br>Approx. 30 lbs | Gaylord Part Number<br>Approx. 200 lbs | Size<br>(in.) | Inside Diameter (in.) |       | Outside Diameter (in.) |       |
|-----------------------------------|--|---------------|-----------------------|-------|------------------------|-------|
|                                   |  |               | Min                   | Max   | Min                    | Max   |
| 06-804S-A                         | 06-LCP-250                             | 1/4           | .237                  | .266  | .375                   | .400  |
| 06-806S-A                         | 06-LCP-350                             | 3/8           | .341                  | .380  | .497                   | .526  |
| 06-808S-A                         | 06-LCP-500                             | 1/2           | .473                  | .516  | .664                   | .700  |
| 06-810S-A                         | 06-LCP-625                             | 5/8           | .603                  | .639  | .805                   | .837  |
| 06-812S-A                         | 06-LCP-750                             | 3/4           | .707                  | .759  | .950                   | .989  |
| 06-814S-A                         | 06-LCP-875                             | 7/8           | .848                  | .898  | 1.107                  | 1.151 |
| 06-816S-A                         | 06-LCP-1000                            | 1             | 1.006                 | 1.055 | 1.267                  | 1.320 |
| 06-820S-A                         | 06-LCP-1250                            | 1-1/4         | 1.199                 | 1.257 | 1.446                  | 1.500 |
| 06-824S-1                         | 06-LCP-1500                            | 1-1/2         | 1.566                 | 1.647 | 1.867                  | 1.947 |

## Ultraflex Split Loom Nylon



### APPLICATION

- Mechanical, chemical and electrical protection where high temperature is required

### CONSTRUCTION

- Material:** Durable Nylon, black with grey stripe
- Temperature:** -40°C to 149°C
- Construction:** Slit allows quick installation without the need of fishing wires
- Feature:** Resistant to oil and gas, moisture, UV light, salt and excellent high temperature and abrasion protection
- Option:** Packaged in 2'sq boxes or 4'sq gaylords. Cut to length packaging also available  
Other colours available upon request  
Non-slit also available (allows for better protection from environmental elements)

| Box Part Number<br>Approx. 30 lbs | Gaylord Part Number<br>Approx. 200 lbs | Size<br>(in.) | Inside Diameter (in.) |       | Outside Diameter (in.) |       |
|-----------------------------------|--|---------------|-----------------------|-------|------------------------|-------|
|                                   |  |               | Min                   | Max   | Min                    | Max   |
| 06-LCN-250-BOX                    | 06-LCN-250                             | 1/4           | .237                  | .266  | .375                   | .400  |
| 06-LCN-350-BOX                    | 06-LCN-350                             | 3/8           | .341                  | .380  | .497                   | .526  |
| 06-LCN-500-BOX                    | 06-LCN-500                             | 1/2           | .473                  | .516  | .664                   | .700  |
| 06-LCN-625-BOX                    | 06-LCN-625                             | 5/8           | .603                  | .639  | .805                   | .837  |
| 06-LCN-750-BOX                    | 06-LCN-750                             | 3/4           | .707                  | .759  | .950                   | .989  |
| 06-LCN-875-BOX                    | 06-LCN-875                             | 7/8           | .848                  | .898  | 1.107                  | 1.151 |
| 06-LCN-1000-BOX                   | 06-LCN-1000                            | 1             | 1.006                 | 1.055 | 1.267                  | 1.320 |
| 06-LCN-1250-BOX                   | 06-LCN-1250                            | 1-1/4         | 1.199                 | 1.257 | 1.446                  | 1.500 |
| 06-LCN-1500-BOX                   | 06-LCN-1500                            | 1-1/2         | 1.566                 | 1.647 | 1.867                  | 1.947 |

Note: All dimensions are nominal and are subject to normal manufacturing tolerance – Specifications are subject to change without prior notice