


Battery Cable SGT



SPECIFICATION

Meets S.A.E. J1127

APPLICATIONS

- Ground or Battery

CONSTRUCTION

Conductor: Stranded bare copper conductors

Insulation: Polyvinyl Chloride (PVC)

Temperature: -40°C to 105°C

Voltage: 600V


Features: Flexible and resistant to oil

Option: Standard colours are red and black; other solid coloured outer jacket available upon request

Part Number	Conductor		Approx. Insulation Thickness (in.)	Approx. Diameter (in.)	Approx Weight (LB/MFT)
	AWG Size	Stranding			
06015-12-010	4	133/23	0.065	0.356	162
06015-13-010	2	259/25	0.065	0.420	236
06015-07-010	1/0	1007/30	0.065	0.515	367
06015-06-010	2/0	1292/30	0.065	0.570	473
06015-04-010	4/0	2090/30	0.078	0.706	758

*Note: All dimensions are nominal and are subject to normal manufacturing tolerance.
Specifications are subject to change without prior notice*

Battery Cable SGX



SPECIFICATION

Meets S.A.E.J1127

CONSTRUCTION

Conductor: Stranded bare copper conductors

Insulation: Cross-linked polyolefin

Temperature: -40°C to 125°C


Voltage: 600V

Features: Resistant to heat, oil, ozone, acid and other chemicals
Good abrasion and cut-through resistant

Option: Standard colours are red and black; other solid coloured outer jacket available upon request

Part Number	Conductor		Approx. Insulation Thickness (in.)	Approx. Diameter (in.)	Approx Weight (LB/MFT)
	AWG Size	Stranding			
17035-10	6	133/27	0.060	0.316	111
17035-11	4	61/22	0.065	0.360	167
17035-13	2	127/23	0.065	0.435	242
17035-14	1	133/22	0.065	0.460	304
17035-15	1/0	1064/30	0.065	0.531	375
17035-16	2/0	1330/30	0.065	0.578	483
17035-18	4/0	2109/30	0.078	0.732	771

Parallel Battery Booster



SPECIFICATION

Meets S.A.E.J1494

APPLICATIONS

- Manufacture of Booster Cable Sets

CONSTRUCTION

Conductor: Stranded bare copper, 2 conductor parallel

Insulation: Polyvinyl Chloride (PVC), black & red

Temperature: -40°C to 80°C

Voltage: 50V

Features: Resistant to oil & gas, UV and abrasion

Packaging: 152m (500 ft) roll

Part Number	Conductor		Approx. Insulation Thickness (in.)	Approx. Diameter (in.)	Approx Weight (LB/MFT)
	AWG Size	Stranding			
08040-03-013	6	266	0.047	0.365 x 0.73	230
08040-04-013	4	399	0.047	0.40 x 0.815	360

*Note: All dimensions are nominal and are subject to normal manufacturing tolerance.
Specifications are subject to change without prior notice.*